

耐磨胶管 ARVAC SW



应用:

■ Artrac胶管, 用于沙子、碎石、水泥、粉煤灰、玻璃、金属、塑料颗粒、化肥、矿盐和浆料等具有磨损性的物料输送作业

Applications:

■ The Artrac® hose is used for a variety of abrasive, material-handling applications to transfer sand, gravel, cement, fly ash, glass, metals, plastic pellets, fertilizers, rock salts and slurries

技术参数:

■ 内层: 热塑性聚氨酯/PVC (聚乙烯) 合金 (具有静电放电/静电导电性)
 ■ 增强层: 硬质高密度PVC (聚乙烯) 螺旋丝
 ■ 外层: 热塑性丁腈、聚氨酯/PVC (聚乙烯) 合金 (非导体) (也提供具有导体性的管外层)
 ■ 温度: -30° F到158° F (34° C到70° C)
 ■ 包装: 1" -6" 100' 倍数长盘卷, 聚乙烯外包装袋; 8" -10" 20' 倍数长盘卷, 聚乙烯外包装袋
 ■ 管标标识: 无商标标识

Technical description:

■ Tube: Thermoplastic alloyed blend of polyurethane and PVC (static dissipating/static conductive)
 ■ Reinforcement: Rigid high-density PVC helix
 ■ Cover: Thermoplastic alloyed blend of nitrile, polyurethane, and PVC (nonconductive) (Available with conductive cover—see order code below)
 ■ Temperature: -40°F to 158°F (-40°C to 70°C)
 ■ Packaging: 1¼"-6" 100' lengths, coiled and polywrapped; 8"-10" 20' lengths, polytube
 ■ Branding: Not branded

耐磨胶管 ARTRAC

产品编码 No.	内径		外径	工作压力	耐负压	弯曲半径	重量
	in	mm	mm	bar	in	mm	kg/m
HM-20448195	1-1/4	31.8	41.4	3.1	29	76	0.51
HM-20448194	1-1/2	38.1	48.0	2.8	29	76	0.60
HM-20448193	2	50.8	62.7	2.8	29	63	1.00
HM-20448192	2-1/2	63.5	77.5	2.4	29	101	1.29
HM-20448191	3	76.2	93.7	2.1	29	152	1.73
HM-20448190	4	101.6	122.2	2.1	29	177	3.21
HM-20447689	5	127.0	146.8	2.1	29	203	3.87
HM-20447688	6	152.4	179.8	1.7	29	203	5.10
HM-20447687	8	203.2	234.2	1.4	29	456	8.69
HM-20447686	10	254.0	284.7	1.4	29	912	11.85